

Bion Products
Dhr. Christ-Jan van Bijnen
Postbus 391
5060 AJ OISTERWIJK
Nederland



Your notice of
28-10-2014

Your reference

Date
19-11-2014

Analysis Report 14.05183.01

Required tests :

BS 5867-2 (2008)

Identification number	Information given by the client	Date of receipt
T1417528	QATAR - treated with FRS-TSN - 375 g/m ²	28-10-2014

Gina Créelle

Order responsible

This report runs to 2 pages and may be reproduced, as long as it is presented in its entire form, without written permission of Centexbel.

The results of the analysis cover the received samples. Centexbel is not responsible for the representativeness of the samples. In assessing compliance with the specifications, we did not take into account the uncertainty on the test results.

VAT BE 0459.218.289

Fin. Acc. 210-0472965-45

IBAN BE44 2100 4729 6545

CENTEXBEL-GENT
Technologiepark 7
BE-9052 Zwijnaarde
Tel. + 32 9 220 41 51 • Fax + 32 9 220 49 55
gent@centexbel.be

CENTEXBEL-VERVIERS
Avenue du Parc 38
BE-4650 Herve (Chaineux)
Tel. + 32 87 32 24 30 Fax + 32 87 34 05 18
chaineux@centexbel.be

Reference: T1417528 - QATAR - treated with FRS-TSN - 375 g/m²

Determination of the flammability of textile fabrics for curtains and drapes

Date of ending the test 19-11-2014
 Standard used EN ISO 15025 (2002)
 Product standard BS 5867-2 (2008)

Deviation from the standard -

Conditioning 20°C, relative humidity 65%

The test specimens have not been cleaned nor submitted to an accelerated ageing procedure.

Flame application time (s) 15

	Length			Width		
	1	2	3	1	2	3
Flame or hole on edge	no	no	no	no	no	no
Flaming debris droplets	no	no	no	no	no	no

Length tests 1 and 3, width test 2 - flame application on the dark side
 Length test 2, width tests 1 and 3 - flame application on the light side

Type B performance requirements

No part of any hole nor any part of the lowest boundary of any flame shall reach the top edge or either vertical edge.

There shall be no separation of any flaming debris droplets

Conclusion Flammability complies with the requirements of BS 5867-2:2008, type "B"